

# SAFETY DATA SHEET

# SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

**Product ID:** CETS-0475 / 0675 / 1275 / 1875 / 2475 / 3675

Product Name: EcoFlash

Revision Date: Sep 23, 2016 Date Printed: Nov 11, 2016

Version: 1.0 Supersedes Date: N.A.

Manufacturer's Name: Mar-flex Waterproofing & Building Products

Address: 500 Business Parkway Carlisle, OH, US, 45005

Emergency Phone: Chem-Trec: 1-800-424-9300

Information Phone Number: 513-422-7285

Fax: 513-422-7282

Product/Recommended Uses:

# **SECTION 2) HAZARDS IDENTIFICATION**

### Classification:

Specific Target Organ Toxicity - Repeated Exposure - Category 2

Carcinogenicity - Category 1B

# Pictograms:



# Signal Word:

Danger

# **Hazardous Statements - Health:**

May cause damage to organs through prolonged or repeated exposure.

May cause cancer.

# **Precautionary Statements - General:**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

# **Precautionary Statements - Prevention:**

Do not breathe dust/fume/gas/mist/vapors/spray.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

## **Precautionary Statements - Response:**

Get Medical advice/attention if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

## **Precautionary Statements - Storage:**

Store locked up.

Keep container tightly closed.

#### **Precautionary Statements - Disposal:**

Dispose of contents/container to disposal recycling center. Waste management should be in full compliance with federal, state and local laws.

### Hazards Not Otherwise Classified (HNOC):

None.

### **SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS**

CAS	Chemical Name	% By Weight
0008052-42-4	BITUMENS	60% - 70%
0014808-60-7	SILICA, CRYSTALLINE	10% - 25%
0009003-55-8	Polymers	0.0% - 10%
0064742-65-0	MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC	0.0% - 5%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

# **SECTION 4) FIRST-AID MEASURES**

### Inhalation:

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If unwell, or exposed and concerned: Get medical advice/attention.

### **Eye Contact:**

If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.

#### **Skin Contact:**

Rinse/wash with lukewarm, gently flowing water and mild soap for 5 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.

### Ingestion:

Rinse mouth. Call a POISON CENTER/doctor if you feel unwell or are exposed and concerned.

### Most Important Symptoms and Effects, Both Acute and Delayed:

Skin contact can cause skin irritation or redness. It may aggravate pre-existing skin conditions.

# Indication of Any Immediate Medical Attention and Special Treatment Needed:

Treat symptomatically.

# **SECTION 5) FIRE-FIGHTING MEASURES**

# Suitable Extinguishing Media:

Dry chemical, foam, carbon dioxide. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Sand or earth may be used for small fires only.

### **Unsuitable Extinguishing Media:**

No data available.

### Specific Hazards in Case of Fire:

Hazardous combustion products can include carbon monoxide, carbon dioxide & hydrocarbons.

Sulfur oxides.

### **Fire-fighting Procedures:**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

## **Special Protective Actions:**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

# **SECTION 6) ACCIDENTAL RELEASE MEASURES**

### **Emergency Procedure:**

ELIMINATE all ignition sources (no smokes, flares, sparks or flames in immediate area).

Isolate hazard area and keep unnecessary people away. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

### **Recommended Equipment:**

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

#### **Personal Precautions:**

Avoid breathing dust. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

### **Environmental Precautions:**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

### Methods and Materials for Containment and Cleaning up:

Collect by vacuuming or sweeping into suitable containers and dispose of in accordance with local regulations.

# **SECTION 7) HANDLING AND STORAGE**

#### General:

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe dusts.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

# **Ventilation Requirements:**

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

# Storage Room Requirements:

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container can retain residue and may be dangerous.

### SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

# Eye protection:

Wear dust-proof goggles.

#### **Skin Protection:**

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory Protection:**

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

# **Appropriate Engineering Controls:**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA STEL (ppm)	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
BITUMENS												1
MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC		2000	500				1					
SILICA, CRYSTALLINE		[10 mg/m3 percent SiO2+2 / 250 percent SiO2+5 mppcf]; [30 mg/m3 percent SiO2+2];	a				[1,3]; [3];	0.05e				1

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH TLV Basis	ACGIH Carcinogen	ACGIH Notations
BITUMENS	0.5				URT & eye irr	A4	A4; BEI
MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC							
SILICA, CRYSTALLINE	0.025 (R)				Pulmonary fibrosis; lung cancer	A2	A2

A2 - Suspected Human Carcinogen, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, irr - Irritation, URT - Upper respiratory tract

# SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

# **Physical and Chemical Properties**

Density 1.00 lb/gal % Solids By Weight N/A
Density VOC 0.00 lb/gal % VOC 0.00%

Specific Gravity 0.12

Appearance Black liable solid rubber

Odor Threshold N/A

Odor Description Light Petroleum

pH N/A

Water Solubility Insoluble in water

N/A Flammability Flash Point Symbol N/A Flash Point N/A Viscosity N/A Lower Explosion Level N/A Upper Explosion Level N/A Vapor Pressure N/A Vapor Density N/A Freezing Point N/A

Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	N.A.
Decomposition Pt	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

# **SECTION 10) STABILITY AND REACTIVITY**

### Stability:

The product is stable under normal storage conditions.

### **Conditions to Avoid:**

Temperatures over 400°F may cause resin degradation.

### Hazardous Reactions/Polymerization:

Will not occur.

### **Incompatible Materials:**

No data available.

# **Hazardous Decomposition Products:**

Carbon monoxide, various hydrocarbons and sulfur oxides.

# **SECTION 11) TOXICOLOGICAL INFORMATION**

# Likely Route of Exposure:

Inhalation, ingestion, skin absorption, eye contact.

# Skin Corrosion/Irritation:

No data available

# Serious Eye Damage/Irritation:

No data available

# Respiratory/Skin Sensitization:

No data available

# **Germ Cell Mutagenicity:**

No data available

# Carcinogenicity:

May cause cancer.

# **Reproductive Toxicity:**

No data available

# **Specific Target Organ Toxicity - Single Exposure:**

No data available

### **Specific Target Organ Toxicity - Repeated Exposure:**

Under extreme and non-normal circumstances such as extensive cutting, grinding and pulverizing, there is some potential exposure to respirable crystalline silica (quartz). Prolonged and frequent exposure to such conditions could in some instances cause silicosis, a fibrosis of the lungs.

May cause damage to organs through prolonged or repeated exposure.

## **Aspiration Hazard:**

No data available

### **Acute Toxicity:**

No data available.

0008052-42-4 BITUMENS

LC50 (Rodent - rat, Inhalation): >94.4 mg/m3, Toxic effects: Details of toxic effects not reported other than lethal dose value.

LD50 (Rodent - rat, Oral): >5000 mg/kg, Toxic effects: Gastrointestinal - hypermotility, diarrhea.

0064742-65-0 MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC

LD50 (Rodent - rat, Oral): >5000 mg/kg, Toxic effects: Details of toxic effects not reported other than lethal dose value.

LD50 (Rodent - rabbit, Administration onto the skin): 5000 mg/kg, Toxic effects: Details of toxic effects not reported other than lethal

#### **Potential Health Effects - Miscellaneous**

0008052-42-4 BITUMENS

Is an IARC carcinogen. Occupational exposures to straight-run bitumens and their emissions during road paving are possibly carcinogenic to humans (Group 2B)

0014808-60-7 SILICA, CRYSTALLINE

Is an IARC, NTP or OSHA carcinogen. Repeated overexposure to crystalline silica may lead to x-ray changes and chronic lung disease. Inhalation of high dust concentrations may cause: breathing difficulties, lung injury. WARNING: This chemical is known to the State of California to cause cancer.

### **Chronic Exposure**

0014808-60-7 SILICA, CRYSTALLINE

Prolonged inhalation of respirable crystalline silica dust can result in lung disease (i.e. silicosis and/or lung cancer). Symptoms include coughing, shortness of breath, wheezing and reduced pulmonary function.

# **SECTION 12) ECOLOGICAL INFORMATION**

#### Toxicity:

No data available

### Persistence and Degradability:

No data available.

# Other Adverse Effects:

No data available.

### **Bio-accumulative Potential**

0064742-65-0 MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC

Contains constituents with the potential to bioaccumulate.

# **Mobility in Soil**

0064742-65-0 MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC

Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.

# **SECTION 13) DISPOSAL CONSIDERATIONS**

## Waste Disposal:

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

# **SECTION 14) TRANSPORT INFORMATION**

# **U.S. DOT Information:**

UN/NA #: Not regulated Proper Shipping Name: Not applicable Hazard Class: Not applicable Packing Group: Not applicable

# **IMDG Information:**

UN/NA #: Not regulated Proper Shipping Name: Not applicable Hazard Class: Not applicable Packing Group: Not applicable Marine Pollutant: No data available

### **IATA Information:**

UN/NA #: Not regulated Proper Shipping Name: Not applicable Hazard Class: Not applicable Packing Group: Not applicable


# **SECTION 15) REGULATORY INFORMATION**

CAS	Chemical Name	% By Weight	Regulation List
0008052-42-4	BITUMENS	60% - 70%	SARA312,IARCCarcinogen,TSCA,TSCA_UVCB - CHEMICAL SUBSTANCES OF UNKNOWN OR VARIABLE COMPOSITION, COMPLEX REACTION PRODUCTS AND BIOLOGICAL MATERIALS
0014808-60-7	SILICA, CRYSTALLINE	10% - 25%	SARA312,IARCCarcinogen,NTPCarcinogen,TSCA,CA_Prop65 - California Proposition 65,CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer
0009003-55-8	Polymers	0.0% - 10%	SARA312,VOC,IARCCarcinogen,TSCA
0064742-65-0	MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT- DEWAXED HEAVY PARAFFINIC	0.0% - 5%	SARA312,TSCA,TSCA_UVCB - CHEMICAL SUBSTANCES OF UNKNOWN OR VARIABLE COMPOSITION, COMPLEX REACTION PRODUCTS AND BIOLOGICAL MATERIALS

# **SECTION 16) OTHER INFORMATION**

### Glossary:

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDGCanadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- ESE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA-National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.



Version 1.0:

Revision Date: Sep 23, 2016

First Edition.

### **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.