



DAMPFUSION



Economical water-based gray acrylic dampproofing

DampFUSION is an excellent acrylic dampproofing membrane. DampFUSION is a fluid applied dampproofing for the exterior of below-grade masonry, block, precast and poured concrete foundation walls. It is designed to stop water vapor and help protect against leaks.



Mar-flex DampFUSION (Water-Based) RWD-01-5 5 Gallon Bucket Each or 36/Pallet



Mar-flex DampFUSION (Water-Based) RWD-01-55 55 Gallon Drum Each or 4/Pallet



Flexible, seamless coating that seals out moisture

DampFUSION Advantages

- Water-based; no odor
- Stops water vapor transmission
- Can be applied to damp walls
- Seamless, monolithic coating
- Gray in color; blends in with concrete
- Can be applied to top of foundation walls
- Surface cures within 24-48 hours

DampFUSION Spec Sheet	
	Water-Based
TOTAL SOLIDS	35-42%
APPLICATION METHOD	spray, brush, or roller
APPLICATION RANGE	50°-100°F
WEIGHT / GALLON	9 lbs.
COVERAGE RATE	115-125 ft.² gal

 $^{^*}$ complete specs at Mar-flex.com

Try the complete line of Mar-flex products.

Foundation Waterproofing | Waterproofing Membranes | Dampproofing Products | Concrete Repair Concrete Anchor Epoxies | Drainage Boards | Egress Window Wells | Standard Window Wells | Sealers/Mastics | Control Joint Systems | Air Barrier Systems | Vortex Vents