

# SAFETY DATA SHEET

---

## SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

---

**Product ID:** IA-68160 A  
**Product Name:** Quick Set Surface Port Paste (Side A)  
**Revision Date:** May 01, 2015 **Date Printed:** Jan 30, 2017  
**Version:** 1.0 **Supersedes Date:** N.A.  
**Manufacturer's Name:** Mar-flex Waterproofing & Building Products  
**Address:** 500 Business Parkway Carlisle, OH, US, 45005  
**Emergency Phone:** Chem-Trec: 1-800-424-9300  
**Information Phone Number:** 513-422-7285  
**Fax:** 513-422-7282  
**Product/Recommended Uses:**

---

## SECTION 2) HAZARDS IDENTIFICATION

---

### Classification:

Specific Target Organ Toxicity -Single Exposure (Respiratory Tract Irritation) - Category 3  
Skin Irritation - Category 2  
Eye Irritation - Category 2A  
Skin Sensitizer - Category 1  
Germ Cell Mutagenicity - Category 2  
Chronic aquatic toxicity - Category 2  
Acute aquatic toxicity - Category 2

### Pictograms:



### Signal Word:

Warning

### Hazardous Statements - Health:

May cause respiratory irritation  
Causes skin irritation  
Causes serious eye irritation  
May cause an allergic skin reaction  
Suspected of causing genetic defects.

### Hazardous Statements - Environmental:

Toxic to aquatic life with long lasting effects

### Precautionary Statements - General:

If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.

**Precautionary Statements - Prevention:**

- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Keep container tightly closed.
- Wash thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Contaminated work clothing should not be allowed out of the workplace.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Avoid release to the environment.

**Precautionary Statements - Response:**

- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- Call a POISON CENTER/doctor,if you feel unwell.
- IF ON SKIN: Wash with plenty of water.
- Specific treatment (see First-aid measures on this SDS).
- If skin irritation occurs: Get medical advice/attention.
- Take off contaminated clothing. And wash it before reuse.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.
- If skin irritation or a rash occurs: Get medical advice/attention.
- IF exposed or concerned: Get medical advice/attention.
- Collect spillage.

**Precautionary Statements - Storage:**

- Store in a well-ventilated place. Store locked up.

**Precautionary Statements - Disposal:**

- Dispose of contents/container to disposal recycling center. Waste management should be in full compliance with federal, state and local laws.

**Hazards Not Otherwise Classified (HNOC):**

- None.

---

**SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS**

---

CAS	Chemical Name	% By Weight
0025068-38-6	BIPHENOL A DIGLYCIDYL ETHER POLYMER	30% - 90%
0014807-96-6	TALC	0.0% - 50%
0002210-79-9	Oxirane, [(2-methylphenoxy)methyl]-	3% - 5%
0067762-90-7	CATALYST AMORPHOUS SILICA	0.0% - 5%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

---

**SECTION 4) FIRST-AID MEASURES**

---

**Inhalation:**

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If unwell, or exposed and concerned : Get medical advice/attention.

**Eye Contact:**

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

**Skin Contact:**

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water and mild soap for 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before re-use.

**Ingestion:**

Rinse mouth. Drink plenty of water and induce vomiting. Obtain immediate medical attention.

**Most Important Symptoms and Effects, Both Acute and Delayed:**

Exposure may cause moderate irritation, sensitization, and dermatitis.

Prolonged contact with the eyes may cause reversible corneal opacity to occur, with no visual impairment expected.

Medical conditions generally aggravated by exposure include: Allergy, eczema, skin conditions

**Indication of Any Immediate Medical Attention and Special Treatment Needed:**

No data available.

---

**SECTION 5) FIRE-FIGHTING MEASURES**

---

**Suitable Extinguishing Media:**

Dry chemical, foam and carbon dioxide is recommended. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

**Unsuitable Extinguishing Media:**

Do not use direct water stream. Since this may cause fire to spread.

**Specific Hazards in Case of Fire:**

Burning produces noxious and toxic fumes.

**Fire-fighting Procedures:**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

**Special Protective Actions:**

Wear NIOSH approved, protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

---

**SECTION 6) ACCIDENTAL RELEASE MEASURES**

---

**Emergency Procedure:**

ELIMINATE all ignition sources (no smokes, flares, sparks or flames in immediate area).

Isolate hazard area and keep unnecessary people away. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Do not touch or walk through spilled material.

If spilled material is cleaned up using a regulated solvent, the resulting mixture may be regulated.

**Recommended Equipment:**

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

**Personal Precautions:**

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

**Environmental Precautions:**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

**Methods and Materials for Containment and Cleaning up:**

Small Spill: Absorb with rag. Wear proper personal protective equipment. Place in a chemical waste container for proper disposal.

Large Spill: Absorb with dry chemical absorbent, earth, sand or any other inert material. Wear proper personal protective equipment. Place in a chemical waster container for proper disposal. Flush contaminated areas with water.

Place spilled material in a container for disposal according to local, state and federal laws and regulations. Dispose via a licensed waster disposal contractor. Contaminated absorbent material may pose the same physical hazards as the product.

## SECTION 7) HANDLING AND STORAGE

### General:

Wash hands after use.  
 Do not get in eyes, on skin or on clothing.  
 Do not breathe vapors or mists.  
 Use good personal hygiene practices.  
 Eating, drinking and smoking in work areas is prohibited.  
 Remove contaminated clothing and protective equipment before entering eating areas.  
 Use disposable containers and paper on work area.

Heating: Use personal protective equipment when transferring material to or from drums, totes or other containers.

### Ventilation Requirements:

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

### Storage Room Requirements:

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, open flame and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous.

Protect from freezing.

Protect from moisture.

## SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

### Eye protection:

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

### Skin Protection:

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Use of barrier cream recommended.

### Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

### Appropriate Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA STEL (ppm)	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
TALC		20 mppcf			1		1					

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH TLV Basis	ACGIH Carcinogen	ACGIH Notations
TALC	2 (E,R)	0.1 f/cc (F) (K)			[LRT irr]; [Pneumoco niosis; lung cancer; mesothelio ma];	[A1]; [A4];	[A1]; [A4];

(F) - Respirable fibers, (K) - Should not exceed 2 mg/m3 respirable particulate mass

---

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

---

### Physical and Chemical Properties

Density	11.02 lb/gal
% Solids By Weight	N/A
Density VOC	0.46 lb/gal
% VOC	0.00%
Specific Gravity	1.32

---

Appearance	White liquid
Odor Threshold	N/A
Odor Description	N/A.
pH	N/A
Water Solubility	Insoluble
Flammability	Flash Point at or above 200 °F
Flash Point Symbol	>
Flash Point	200 °F
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Pressure	>1 TORR @ 356°F (180°C)
Vapor Density	>1
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	392 °F
High Boiling Point	N/A
Auto Ignition Temp	N.A.
Decomposition Pt	N/A
Evaporation Rate	< 1
Coefficient Water/Oil	N/A

---

## SECTION 10) STABILITY AND REACTIVITY

---

### Stability:

The product is stable under normal storage conditions.

### Conditions to Avoid:

Avoid heat, sparks, flame, high temperature, and container contamination.

### Hazardous Reactions/Polymerization:

No data available.

### Incompatible Materials:

Strong oxidizing agents, strong acids and bases.

### Hazardous Decomposition Products:

Carbon monoxide, carbon dioxide, aldehydes and other organics.

---

## SECTION 11) TOXICOLOGICAL INFORMATION

---

### Likely Route of Exposure:

Inhalation, ingestion, skin absorption, eye contact.

### Skin Corrosion/Irritation:

Causes skin irritation

**Serious Eye Damage/Irritation:**

Causes serious eye irritation

**Respiratory/Skin Sensitization:**

May cause an allergic skin reaction

**Germ Cell Mutagenicity:**

Suspected of causing genetic defects.

**Carcinogenicity:**

No data available

**Reproductive Toxicity:**

No data available

**Specific Target Organ Toxicity - Single Exposure:**

May cause respiratory irritation

**Specific Target Organ Toxicity - Repeated Exposure:**

No data available

**Aspiration Hazard:**

No data available

**Acute Toxicity:**

No data available

**Potential Health Effects - Miscellaneous**

0025068-38-6 BISPENOL A DIGLYCIDYL ETHER POLYMER

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guin

---

**SECTION 12) ECOLOGICAL INFORMATION**

---

**Toxicity:**

Toxic to aquatic life with long lasting effects

**Persistence and Degradability:**

No data available.

**Bio-accumulative Potential:**

No data available.

**Mobility in Soil:**

No data available.

**Other Adverse Effects:**

No data available.

---

**SECTION 13) DISPOSAL CONSIDERATIONS**

---

**Waste Disposal:**

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Chemical additions, processing, storage, or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate. Waste characterization and disposal compliance is the responsibility solely of the party generating the waste or deciding to discard or dispose of the material.

---

**SECTION 14) TRANSPORT INFORMATION**

---

**U.S. DOT Information:**

UN number: N/A  
Proper shipping name: N/A (N/A)  
Hazard class: N/A  
Packaging group: N/A  
Hazardous substance (RQ): No data available  
Toxic-Inhalation Hazard: No data available  
Marine Pollutant: No data available  
Note / Special Provision: No data available

**IMDG Information:**

UN number: UN3082  
Proper shipping name: Environmentally hazardous substances, liquid, n.o.s. (BISPHENOL A DIGLYCIDYL ETHER POLYMER, Oxirane, [(2-methylphenoxy)methyl]-)  
Hazard class: 9  
Packaging group: III  
Marine Pollutant: No data available  
Note / Special Provision: No data available

**IATA Information:**

UN number: UN3082  
Hazard class: 9  
Packaging group: III  
Proper shipping name: Environmentally hazardous substances, liquid, n.o.s. (BISPHENOL A DIGLYCIDYL ETHER POLYMER, Oxirane, [(2-methylphenoxy)methyl]-)  
Note / Special Provision: No data available

---

**SECTION 15) REGULATORY INFORMATION**

---

**California Proposition 65:**

In order to comply with California Proposition 65, we feel obligated to advise that some of our products may conceivably contain trace contaminants of some of the listed chemicals. While not necessarily added to our products as ingredients, some listed chemicals may be present in the raw materials from suppliers and over which we have no control. Therefore, even though some of the listed substances may not be present, a significant risk as defined by the regulations in order to comply with California law, we feel obligated to make the following statement:

WARNING: Our products may contain trace amounts of some chemicals considered by the State of California to be carcinogens or reproductive toxicants.

CAS	Chemical Name	% By Weight	Regulation List
0025068-38-6	BISPHENOL A DIGLYCIDYL ETHER POLYMER	30% - 90%	SARA312,TSCA
0014807-96-6	TALC	0.0% - 50%	SARA312,IARCCarcinogen,TSCA
0002210-79-9	Oxirane, [(2- methylphenoxy)methyl]-	3% - 5%	SARA312,VOC,TSCA
0067762-90-7	CATALYST AMORPHOUS SILICA	0.0% - 5%	SARA312,TSCA,TSCA_UVCB - CHEMICAL SUBSTANCES OF UNKNOWN OR VARIABLE COMPOSITION, COMPLEX REACTION PRODUCTS AND BIOLOGICAL MATERIALS


---

## SECTION 16) OTHER INFORMATION

---

### Glossary:

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- ESE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.



( \* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

### Version 1.0:

Revision Date: May 01, 2015

First Edition.

---

## DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.



# SAFETY DATA SHEET

---

## SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

---

**Product ID:** IA-68160 B  
**Product Name:** Quick Set Surface Port Paste (Side B)  
**Revision Date:** May 01, 2015 **Date Printed:** Feb 08, 2017  
**Version:** 1.0 **Supersedes Date:** N.A.  
**Manufacturer's Name:** Mar-flex Waterproofing & Building Products  
**Address:** 500 Business Parkway Carlisle, OH, US, 45005  
**Emergency Phone:** Chem-Trec: 1-800-424-9300  
**Information Phone Number:** 513-422-7285  
**Fax:** 513-422-7282  
**Product/Recommended Uses:**

---

## SECTION 2) HAZARDS IDENTIFICATION

---

**Classification:**

- Specific Target Organ Toxicity - Repeated Exposure - Category 2
- Skin Corrosion - Category 1B
- Serious Eye Damage - Category 1
- Respiratory Sensitizer (Solid/Liquid) - Category 1
- Skin Sensitizer - Category 1
- Flammable Liquids - Category 4
- Corrosive to metals - Category 1
- Acute toxicity Oral - Category 5

**Pictograms:**



**Signal Word:**

Danger

**Hazardous Statements - Physical:**

- May be corrosive to metals
- Combustible Liquid

**Hazardous Statements - Health:**

- May cause damage to organs through prolonged or repeated exposure.
- Causes severe skin burns and eye damage
- Causes serious eye damage
- May cause allergy or asthma symptoms or breathing difficulties if inhaled
- May cause an allergic skin reaction
- May be harmful if swallowed

**Precautionary Statements - General:**

- If medical advice is needed, have product container or label at hand.

Keep out of reach of children.  
Read label before use.

**Precautionary Statements - Prevention:**

- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wash thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- [In case of inadequate ventilation] wear respiratory protection.
- Contaminated work clothing should not be allowed out of the workplace.
- Keep only in original packaging.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Precautionary Statements - Response:**

- Get Medical advice/attention if you feel unwell.
- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- Wash contaminated clothing before reuse.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- Immediately call a POISON CENTER or doctor.
- Specific treatment (see First-aid measures on this SDS).
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- IF ON SKIN: Wash with plenty of water.
- If skin irritation or a rash occurs: Get medical advice/attention.
- Absorb spillage to prevent material damage.
- In case of fire: Use dry chemical, carbon dioxide, foam to extinguish.
- Call a POISON CENTER/doctor, if you feel unwell.

**Precautionary Statements - Storage:**

- Store locked up.
- Store in a corrosive resistant container with a resistant inner liner
- Store in a well-ventilated place.

**Precautionary Statements - Disposal:**

Dispose of contents/container to disposal recycling center. Waste management should be in full compliance with federal, state and local laws.

**Hazards Not Otherwise Classified (HNOC):**

None.

**Acute toxicity of 33.91% of the mixture is unknown**

---

**SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS**

---

CAS	Chemical Name	% By Weight
0013983-17-0	WOLLASTONITE	40% - 50%
Trade Secret	Proprietary Polymercaptan	15% - 25%
Proprietary	Polyamine	5% - 10%
0014807-96-6	TALC	0.0% - 10%
0008002-09-3	PINE OIL	3% - 7%
Trade Secret	Furfuryl Alcohol	1.0% - 5%
0067762-90-7	CATALYST AMORPHOUS SILICA	0.0% - 5%
0000111-40-0	DIETHYLENE TRIAMINE	0.0% - 5%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

---

## SECTION 4) FIRST-AID MEASURES

---

### **Inhalation:**

Eliminate all ignition sources if safe to do so. Remove source of exposure or move person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor.

### **Eye Contact:**

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 30 minutes or until medical aid is available. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately call a POISON CENTER or doctor, preferably an eye specialist.

### **Skin Contact:**

Take off immediately all contaminated clothing, shoes, and leather goods (e.g., watchbands, belts). Wash with plenty of lukewarm, gently flowing water for duration of 30 minutes or until medical aid is available. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before re-use or discard.

### **Ingestion:**

Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. If vomiting occurs naturally, lie on your side, in the recovery position.

### **Most Important Symptoms and Effects, Both Acute and Delayed:**

Medical conditions generally aggravated by exposure include: Dermatitis, reproductive, asthma, bronchitis, and inflammatory or fibrotic respiratory disease.

Contact of undiluted product with the eyes or skin quickly causes severe irritation and pain and may cause burns, necrosis and permanent injury. Burns of the eye may cause blindness.

Inhalation of aerosols and mists may severely damage contacted tissue and produce scarring.

Product is readily absorbed through the skin and may cause nausea, headache and general discomfort.

Prolonged or repeated skin contact may defat the skin and cause dermatitis; allergic reactions may arise in sensitive individuals.

### **Indication of Any Immediate Medical Attention and Special Treatment Needed:**

No data available.

---

## SECTION 5) FIRE-FIGHTING MEASURES

---

### **Suitable Extinguishing Media:**

Dry chemical, foam, carbon dioxide water spray or fog is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

### **Unsuitable Extinguishing Media:**

Do not use direct water stream. Since this may cause fire to spread.

### **Specific Hazards in Case of Fire:**

May produce irritation or poisonous gases.

### **Fire-fighting Procedures:**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Isolate for ½ mile in all directions if tank, rail car or tank truck is involved in fire.

If runoff from fire control occurs, notify the appropriate authorities.

### **Special Protective Actions:**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

---

## SECTION 6) ACCIDENTAL RELEASE MEASURES

---

### **Emergency Procedure:**

ELIMINATE all ignition sources (no smokes, flares, sparks or flames in immediate area).

Isolate hazard area and keep unnecessary people away. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Do not touch or walk through spilled material.

If spilled material is cleaned up using a regulated solvent, the resulting mixture may be regulated.

**Recommended Equipment:**

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

**Personal Precautions:**

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

**Environmental Precautions:**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

**Methods and Materials for Containment and Cleaning up:**

Contain and collect spilled materials with non-combustible, absorbent material and place in a container for disposal according to local regulations. Dispose via a licensed waster disposal contractor. Contaminated absorbent material may pose the same physical hazards as the product.

---

**SECTION 7) HANDLING AND STORAGE**

---

**General:**

Wash hands after use.  
Do not get in eyes, on skin or on clothing.  
Do not breathe vapors or mists.  
Use good personal hygiene practices.  
Eating, drinking and smoking in work areas is prohibited.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Eyewash stations and showers should be available in areas where this material is used and stored.

**Ventilation Requirements:**

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

**Storage Room Requirements:**

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous.  
Do not cut, drill, grind, weld or perform similar operations on or near containers. Empty containers may contain explosive vapors.  
Protect from freezing.  
Protect from moisture.

---

**SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

**Eye protection:**

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids.If additional protection is needed for entire face, use in combination with a face shield.

**Skin Protection:**

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

**Respiratory Protection:**

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers. Use NIOSH-approved respirator for organic vapor and mist.

**Appropriate Engineering Controls:**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA STEL (ppm)	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
---------------	-----------------	------------------	----------------	-------------------	-----------------	-----------------------	--------------------------	-------------------	-----------------	--------------------	------------------	------------------

DIETHYLENE TRIAMINE							4	1			
TALC		20 mppcf			1		1				

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH TLV Basis	ACGIH Carcinogen	ACGIH Notations
DIETHYLENE TRIAMINE	4.2	1			URT & eye irr		Skin
TALC	2 (E,R)	0.1 f/cc (F) (K)			[LRT irr]; [Pneumococcosis; lung cancer; mesothelioma];	[A1]; [A4];	[A1]; [A4];

(F) - Respirable fibers, (K) - Should not exceed 2 mg/m3 respirable particulate mass, irr - Irritation, URT - Upper respiratory tract

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

Density	12.94 lb/gal
% Solids By Weight	N/A
Density VOC	1.18 lb/gal
% VOC	0.00%
Specific Gravity	1.55

Appearance	Grey-black paste
Odor Threshold	pinc - 0.1
Odor Description	Amine/skunk like
pH	N/A
Water Solubility	Appreciable
Flammability	Flashpoints at or above 100 °F and less than 200 °F
Flash Point Symbol	N/A
Flash Point	172 °F
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Pressure	1 mmHg
Vapor Density (air = 1)	> 1
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	414 °F
High Boiling Point	N/A
Auto Ignition Temp	N.A.
Decomposition Pt	N/A
Evaporation Rate (n-butyl acetate = 1)	< 1
Coefficient Water/Oil	N/A

## SECTION 10) STABILITY AND REACTIVITY

### Stability:

The product is stable under normal storage conditions.

### Conditions to Avoid:

Avoid heat, sparks, flame, high temperature, freezing and contact with incompatible materials.

**Hazardous Reactions/Polymerization:**

N-Nitrosamines, many of which are known to be potent carcinogens, may be formed when the product comes in contact with nitrous acid, nitrites or atmospheres with high nitrous oxide concentrations. Product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Materials reactive with hydroxyl compounds. Nitrites, nitrosating agents. A reaction accompanied by large heat release occurs when the product is mixed with acids. Heat generated may be sufficient to cause vigorous boiling creating a hazard due to splashing or splattering of hot material.

**Incompatible Materials:**

Mineral acids, organic acids, oxidizing agents, reactive metals, sodium or calcium hypochlorite.

**Hazardous Decomposition Products:**

Ammonia, oxides of nitrogen, carbon oxide and monoxide, nitric acid.

---

**SECTION 11) TOXICOLOGICAL INFORMATION**

---

**Likely Route of Exposure:**

Inhalation and skin absorption

**Skin Corrosion/Irritation:**

Causes severe skin burns and eye damage

**Serious Eye Damage/Irritation:**

Causes serious eye damage

**Respiratory/Skin Sensitization:**

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

**Germ Cell Mutagenicity:**

No data available

**Carcinogenicity:**

No data available

**Reproductive Toxicity:**

No data available

**Specific Target Organ Toxicity - Single Exposure:**

No data available

**Specific Target Organ Toxicity - Repeated Exposure:**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration Hazard:**

No data available

**Acute Toxicity:**

No data available

0000111-40-0 DIETHYLENE TRIAMINE

LD50 (oral, rat): 1080 mg/kg body weight (1)  
LD50 (oral, rat): 1800 mg/kg body weight (2)  
LD50 (oral, rat): 2330 mg/kg body weight (3)  
LD50 (dermal, rabbit): 1046 mg/kg (1090 mL/kg) (3)  
LD50 (dermal, guinea pig): 163 mg/kg (170 mL/kg) (4-day appl)

**Potential Health Effects - Miscellaneous**

0013983-17-0 WOLLASTONITE

The following medical conditions may be aggravated by exposure: asthma, lung disease, respiratory disease.

Long-term respiratory exposure exceeding TLV may damage the lungs, leading to bronchitis and impairment of lung capacity.

---

**SECTION 12) ECOLOGICAL INFORMATION**

---

**Toxicity:**

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

**Persistence and Degradability:**

No data available.

**Bio-accumulative Potential:**

No data available.

**Mobility in Soil:**

No data available.

**Other Adverse Effects:**

No data available.

---

**SECTION 13) DISPOSAL CONSIDERATIONS**

---

**Waste Disposal:**

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

The generation of waste should be avoided or minimized whenever possible. Chemical waste, even small quantities, should never be poured down drains, sewers or waterways.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Chemical additions, processing, storage, or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate. Waste characterization and disposal compliance is the responsibility solely of the party generating the waste or deciding to discard or dispose of the material.

---

**SECTION 14) TRANSPORT INFORMATION**

---

**U.S. DOT Information:**

UN number: N/A  
Proper shipping name: N/A (N/A)  
Hazard class: N/A  
Packaging group: N/A  
Hazardous substance (RQ): No data available  
Toxic-Inhalation Hazard: No data available  
Marine Pollutant: No data available  
Note / Special Provision: No data available

**IMDG Information:**

UN number: UN1760  
Proper shipping name: Corrosive liquids, n.o.s. (N/A)  
Hazard class: 8  
Packaging group: II  
Marine Pollutant: No data available  
Note / Special Provision: No data available

**IATA Information:**

UN number: UN1760  
Hazard class: 8  
Packaging group: II  
Proper shipping name: Corrosive liquids, n.o.s. (N/A)  
Note / Special Provision: No data available

---

**SECTION 15) REGULATORY INFORMATION**

---

**California Proposition 65:**

In order to comply with California Proposition 65, we feel obligated to advise that some of our products may conceivably contain trace contaminants of some of the listed chemicals. While not necessarily added to our products as ingredients, some listed chemicals may be present in the raw materials from suppliers and over which we have no control. Therefore, even though some of the listed substances may not be present, a significant risk as defined by the regulations in order to comply with California law, we feel obligated to make the following statement:

WARNING: Our products may contain trace amounts of some chemicals considered by the State of California to be carcinogens or reproductive toxicants.

CAS	Chemical Name	% By Weight	Regulation List
0013983-17-0	WOLLASTONITE	40% - 50%	SARA312,IARCCarcinogen
0014807-96-6	TALC	0.0% - 10%	SARA312,IARCCarcinogen,TSCA
0008002-09-3	PINE OIL	3% - 7%	SARA312,VOC,TSCA,TSCA_UVCB - CHEMICAL SUBSTANCES OF UNKNOWN OR VARIABLE COMPOSITION, COMPLEX REACTION PRODUCTS AND BIOLOGICAL MATERIALS
0067762-90-7	CATALYST AMORPHOUS SILICA	0.0% - 5%	SARA312,TSCA,TSCA_UVCB - CHEMICAL SUBSTANCES OF UNKNOWN OR VARIABLE COMPOSITION, COMPLEX REACTION PRODUCTS AND BIOLOGICAL MATERIALS
0000111-40-0	DIETHYLENE TRIAMINE	0.0% - 5%	SARA312,VOC,TSCA

## SECTION 16) OTHER INFORMATION

### Glossary:

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- ESE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

### HMIS

Health	* 3
FLAMMABILITY	2
Physical Hazard	4
Personal Protection	H

(\* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

### Version 1.0:

Revision Date: May 01, 2015

First Edition.

## DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.