



MATERIAL SAFETY DATA SHEET

Shockwave Drainage & Insulation Board

1. Product And Company Identification

Supplier

Mar-flex Waterproofing & Building Products
500 Business Parkway
Carlisle, OH 45005 USA

Telephone Number: 513-422-7285
FAX Number: 513-422-7282
E-Mail: info@mar-flex.com
Web Site: www.mar-flex.com

Manufacturer

Mar-flex Waterproofing & Building Products
500 Business Parkway
Carlisle, OH 45005 USA

Telephone Number: 513-422-7285
FAX Number: 513-422-7282
E-Mail: info@mar-flex.com
Web Site: www.mar-flex.com

Supplier Emergency Contacts & Phone Number

Chem-Trec: 1-800-424-9300

Manufacturer Emergency Contacts & Phone Number

Chem-Trec: 1-800-424-9300

Issue Date: 10/27/2014

Product Name: Shockwave Drainage & Insulation Board

CAS Number: Not Established

MSDS Number: 125

Product Code: DM-48325, -48350

Product/Material Uses - Designed to be used as a below-grade foundation drainage/insulation board.

Product Identification Text - 1" or 2" x 3' x 4' Drainage/Insulation Board

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
POLYETHYLENE-POLYOLEFIN FOAM WASTE	Not Establis	0 - 100

3. Hazards Identification

This product does not meet the definition given in 29 CFR Part 1910.1200 (OSHA). Information is furnished as a customer service.

4. First Aid Measures

No Data Available...

5. Fire Fighting Measures

Flash Point: 420-440 °C

Extinguishing Media - Dry powder, CO2 (Carbon dioxide), Water Spray Jet

Fire Fighting Instructions - Fire fighters shall use breathing apparatus with independent air supply.

In the event of a fire the following can be released: Carbon Monoxide (CO) and/or Carbon Dioxide (CO2)

6. Accidental Release Measures

No Data Available...

7. Handling And Storage

Handling And Storage Precautions - No special instructions or requirements. Protect against fire, material is combustible.

Work/Hygienic Practices - Avoid contact of molten material with skin.

8. Exposure Controls/Personal Protection

No Data Available...

MATERIAL SAFETY DATA SHEET

Shockwave Drainage & Insulation Board

9. Physical And Chemical Properties

Appearance - Multi-colored

Odor - None

Chemical Type: Pure

Physical State: Solid

Melting Point: 110 - 150 °C

Packing Density: 4-6 lbs per cu/ft

Solubility: Inert

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Hazardous Decomposition Products - Carbon Monoxide (CO)

11. Toxicological Information

No Data Available...

12. Ecological Information

No Data Available...

13. Disposal Considerations


Product can be placed in a landfill, or dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

No Data Available...

15. Regulatory Information

No Data Available...

NFPA	HMIS
	HEALTH 0
	FLAMMABILITY 1
	REACTIVITY 0
	PERSONAL PROTECTION <input type="text"/>

16. Other Information

No Data Available...

Disclaimer

The above information pertains to this product as currently formulated and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product.

Mar-flex Waterproofing & Building Products makes no warranties, express or implied and assumes no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

Mar-flex Building Solutions