



MAR-FLEX FOUNDATION CRACK INJECTION AND REPAIR

Stacked Foundation?

Don't Tackle A Job Without Mar-flex At Your Side.

Mar-flex Crack Repair Products

Crack Injection Repair Kits, Stitch Kits, Urethanes, Epoxies, Port Pastes, Accessories

Try the complete line of Mar-flex products.

Foundation Waterproofing Waterproofing Membranes Dampproofing Products Concrete Repair Concrete Anchor Epoxies Drainage Boards Egress Window Wells Standard Window Wells Sealers/Mastics Control Joint Systems Air Barrier Systems Vortex Vents





Place Drop Cloth on floor infront of work area. Clean surface around crack using wire brush.



Prepare Adhesive mixing equal parts of Crack Seal Port Adhesive Part A & Crack Seal/Port Adhesive Part B.

5.



IAT-64250 *Epoxy Repair Kit IAT-64255 *Special Order Only

length of the crack. Let cure about 2-3 hours (until

Place the Mar-flex Injection

Cartridge in your caulking gun. Attach Mixing Nozzle,

Attach to lowest Port and

Nut and Hose Assembly.

fingernail hard.)

begin injecting.

This Mar-flex Polyurethane kit includes all of the materials and accessories for low-pressure injection and repair of 6-8 linear feet of crack.

- 1, 8 oz. jar of Crack Seal and Port Adhesive, Part A
- 1, 8 oz. jar of Crack Seal and Port Adhesive, Part B
- 2 wooden sticks
- 15 surface ports and caps
- 2 single cartridges of Mar-flex Injection Foam Polyurethane Resin
- 2 (3/8": 24) mixing nozzles for mixing Injection Resin
- 1 injection hose assembly with white plastic shut-off valve
- 2 pair nitrile gloves
- Wire brush
- Safety goggles
- 1 plastic trowel
- 1 drop cloth
- Printed instructions & link to online ihow-to video
- Product Data & SDS Sheets

You'll also need:

- Standard single caulking gun
- Scrap cardboard for mixing Surface Seal and Port Adhesive
- Clean plastic bottle filled with 1-2 cups of water

CONTRACTOR CRACK INJECTION 30' START-UP KIT



Everything the contractor needs to repair foundation cracks!



Everything you need to repair foundation cracks up to 30 linear feet

The Mar-flex Crack Injection Start-Up Kit contains all the materials and supplies necessary to repair foundation cracks.

Mar-flex Crack Injection Start-Up Kit Advantages

- Repairs up to 30 lineal feet of foundation cracks
- Easy to use
- Fixes hairline cracks to actively leaking cracks
- Additional concrete repair products available

Mar-flex Crack Injection Start-Up Kit includes:

- 1 Dual Cartridge Crack Injection Gun
- 3 Dual Cartridge Quick Set Surface Port Paste
- 3 Dual Cartridge Quick Foam Fine
- 1 Quick Set Urethane Adhesive
- 3 Static Mixers
- 3 Retaining Nuts
- 50 Quick Port Surface Mounts
- 10 Quick Port Corner Mounts
- 4 Quick Hose Injection Assembly
- 1 Safety Goggles
- 5 pair Gloves
- 1 Plastic Trowel
- 1 Wire Brush
- 1 Tool Box

MAR-FLEX CRACK INJECTION ACCESSORIES

The items below are all accessories that are used when repairing concrete and are listed here for your convenience.



Quick Foam Fine Urethane IA-68100

6 (1:1 cartridges)/box A hydrophobic polyurethane liquid formula designed to prevent water from penetrating cracks. Best suited for dry or damp hairline or larger cracks not actively leaking

Quick Foam Broad Urethane IA-68120

6 (1:0 cartridges)/box Designed to stop water infiltration or ex-filtration Best suited for actively leaking cracks that are 1/8" or wider

Ouickset Surface Port Paste

IA-68160 Two component smooth epoxy adhesive designed to seal the surface of a crack and to attach ports to masonrv surfaces. 6 (1:1 cartridges)/box

QuickSet Surface Seal & Peel IA-68165

Two component, solvent free, paste adhesive. It is used as a fast-curing removable surface sealer and to attach ports in epoxy and urethane foam crack repair. Cured product does not require sanding or grinding for removal from the wall. 6 (1:1 cartridges)/box

1/4" : 32 Quick Mix Static Mixer IA-68190

24/box Designed to be used with cartridge systems Recommended to be used with Low Viscosity Epoxy Crack Filler (IA-68140)



Low Viscosity Epoxy Crack Filler IA-68140

8 (2:1 cartridges)/box Prevents movement along cracked surfaces and protects cracks from absorbing water and other substances

For the injection of dry or damp cracks that are hairline and larger

Retaining Nuts IA-68210

Threaded nuts to hold

mixing nozzle onto dual

cartridge during crack

injection process

10/bag

	1
AN ROLL	1
	r
ALC: BAL	Т
	а
	b
	n

Anchor Epoxy IA-68170 2 (1:1 cartridges)/box 2 static mixing nozzles & etaining nuts included Two-component epoxy dhesive. Ideal for anchoring olts, dowels and reinforcing rebar in concrete *Special Order Only

Univeral Ports IA-68280

mounted low pressure

crack injection. Surface/

both epoxy and urethane

materials. Flush mounts to

both flatnd corner concrete

Designed for surface/corner

corner ports are suitable for

24/box Designed to be used with cartridge systems

Mixer IA-68180

1/4": 24 Quick Mix Static

Recommended to be used with Quick Foam Fine (IA-68100), Quick Foam Broad (IA-68120)

Flexible Ouick Hose

Injection Assembly

reach injection ports.

Can be used with either

Use to get to those hard to

epoxy or urethane materials

IA-68220

10/box

Low-Pressure Drill-In Port IA-68230

100/bag To be used on hairline and actively leaking cracks Requires a 5/8" diameter drilled hole Internal ball bearing prevents back-flow of material during injection

Hypo-Allergenic Gloves





Putty Knives IAT-64210

25/box 1.5" plastic, disposable putty knives Ideal for hand mixing and applying surface port paste



Stir Dish IAT-64215

surfaces.

250/box

200/box Clear stir dishes Suitable for mixing surface port paste



Wall Preparation Brush

Composite handle wire

Removes loose and scaled material from both smooth and rough masonry surfaces

Crack Injection Dual Cartridge Gun Economy IAT-64114

Easy front loading with rear tube seals to prevent leaking Kit included to convert gun from 1:1 to 2:1 applications







Questions? Call Mar-flex Today!

800 498 1411

Possible Directions of Wall or Floor Movement



Thermal Changes (Opening & Closing)



Uneven Loading and Settling of Footing



Soil Pressure

Soil Shrinkage

Carbon Fiber Stitches

Mar-flex Stitch Kits

Mar-flex Grids are a pre-impregnated, bidirectional carbon fiber grid for use as a near surface reinforcement for crack stitching and strengthening of concrete foundation structures. The grids are installed using Mar-flex resin to form a carbon fiber reinforced polymer system.

USES:

- Structural Retrofit & Upgrades
- Crack reinforcement & strengthening (increasing service life)
- Use on concrete foundation walls and floors

IA-68166 Stitch Kit (Single)



10' Stitch Kit Single The Single-Stitch Kit is designed to reinforce up to 10' of lineal crack. **Kit Contents:** Carbon fiber stitches (5) Tubeset of hi-mod gel (1) Green sulzer mixers (2)

IA-68167 Stitch Kit (Triple)



30' Stitch Kit Triple The Triple-Stitch Kit is designed to reinforce up to 30' of lineal crack. **Kit Contents:** Carbon fiber stitches (15) Tubeset of hi-mod gel (3) Green sulzer mixers (6)

*Dual Cartridge Gun Required for Gel Resin